

## Comparison table

|  | Robotrad-p+   | Robotrad-p+ Automatic | Robotrad-p+ Variomatic |
|--|---------------|-----------------------|------------------------|
| <b>Standard</b>  |               |                       |                        |
| Operated by joy-stick or touch control panel                       | •             | •                     | •                      |
| Stainless steel top plate  | •             | •                     | •                      |
| Removable side panels  | •             | •                     | •                      |
| Synthetic food approved press plate                                | •             | •                     | •                      |
| Swivel wheels with brake   | •             | •                     | •                      |
| Front handles for easy movability                                  | •             | •                     | •                      |
| Door with safety switches  | •             | •                     | •                      |
| Press-only function (as dough or butter press)                     | •             | •                     | •                      |
| One-touch automatic work cycle                                     | -             | •                     | •                      |
| Auto release of the lid  | -             | •                     | •                      |
| Self-locking, auto start of work cycle and self-opening of the lid | -             | -                     | •                      |
| Adjustable pressing time   | -             | -                     | •                      |
| Variable hydraulic pressure regulation                             | -             | -                     | •                      |
| Memory for 10 pressing and dividing programmes                     | -             | -                     | •                      |
| <b>Options</b>   |               |                       |                        |
| Teflon coated stainless steel top plate                            | •             | •                     | •                      |
| Variable hydraulic pressure regulation                             | •             | •                     | s                      |
| Transformer for 4 wire connections without N at 400 V              | •             | •                     | •                      |
| Storage hooks for up to 6 grids on one or both sides               | •             | •                     | •                      |
| Flour tray with top cover on various positions                     | •             | •                     | •                      |
| Stainless steel support table on left or right side                | •             | •                     | •                      |
| Glass panel with touch controls for extra hygiene                  | •             | •                     | •                      |
| Safety switches on front and removable side panels                 | •             | •                     | •                      |
| Cast iron foot on wheels for extra stability                       | •             | •                     | •                      |
| <b>Accessories</b>   |               |                       |                        |
| Recommended spare parts for 3 years operation                      | •             | •                     | •                      |
| Pressure gauge for hydraulic system                                | •             | •                     | •                      |
| Lower press plate  | •             | •                     | •                      |
| Soft press carpet  | •             | •                     | •                      |
| <b>Power, dimensions &amp; weights</b>                             |               |                       |                        |
| Power (kW)   | 1.6           | 1.6                   | 1.6                    |
| Dimensions WxDxH (cm)  | 82 x 66 x 108 | 82 x 66 x 108         | 82 x 66 x 108          |
| Weight (kg)  | 370           | 370                   | 370                    |

s = standard